according to Regulation (EC) No 1907/2006

C-Quartz UK

Revision date: 28.12.2017 Product code: Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

C-Quartz UK

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Automotive care products

Uses advised against

Any non-intended use.

1.3. Details of the supplier of the safety data sheet

Company name: carpro trading ltd.

Street: 7, Lfigeneias 4th floor strovolos
Place: 1687 Nicosia (CYPRUS)
Responsible Department: +972 546 411 911

1.4. Emergency telephone +972 546 411 911

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Flammable liquid: Flam. Liq. 3 Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - repeated exposure: STOT RE 2 Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

Flammable liquid and vapour.

Causes skin irritation.

Causes serious eye irritation.

May cause damage to organs through prolonged or repeated exposure.

Harmful to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

Stoddard solvent; Low boiling point naphtha - unspecified

Signal word: Warning

Pictograms:







Hazard statements

H226 Flammable liquid and vapour. H315 Causes skin irritation.

H319 Causes serious eye irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

according to Regulation (EC) No 1907/2006

	C-Quartz UK				
Revision date: 28.12.2017	Product code:	Page 2 of 12			
P102	Keep out of reach of children.				
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.				
P260	Do not breathe dust/fume/gas/mist/vapours/spray.				
P264	Wash hands thoroughly after handling.				
P403+P235	Store in a well-ventilated place. Keep cool.				
P501	Dispose of contents/container to local/regional/national/international regulations.				

2.3. Other hazards

In use, may form flammable/explosive vapour-air mixture.

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name			Quantity	
	EC No	Index No	REACH No		
	Classification according to Reg	gulation (EC) No. 1272/2008	[CLP]		
69430-37-1	Aminoalkoxydimethylpolysiloxa	ane		35 - 45 %	
	Flam. Liq. 2, Skin Irrit. 2, Eye I	rrit. 2; H225 H315 H319	•		
8052-41-3	Stoddard solvent; Low boiling	point naphtha - unspecified		1 - < 5 %	
	232-489-3	649-345-00-4			
	Flam. Liq. 3, STOT RE 1, Asp.	Tox. 1, Aquatic Chronic 2; H	226 H372 H304 H411		
67-56-1	methanol			1 - < 5 %	
	200-659-6	603-001-00-X			
	Flam. Liq. 2, Acute Tox. 3, Acu	te Tox. 3, Acute Tox. 3, STO	TSE 1; H225 H331 H311 H301 H370		
83048-65-1	Heptadecafluorodecyltrimethox	1 - < 5 %			
	Skin Irrit. 2, Eye Irrit. 2, STOT	SE 3; H315 H319 H335			
546-68-9	Titanium tetraisopropanolate			1 - < 5 %	
	208-909-6				
	Flam. Liq. 3, Eye Irrit. 2, STOT	SE 3; H226 H319 H336			
556-67-2	octamethylcyclotetrasiloxane				
	209-136-7	014-018-00-1			
	Repr. 2, Aquatic Chronic 4; H361f *** H413				

Full text of H and EUH statements: see section 16.

Further Information

Stoddard Solvent (INDEX no.: 649-345-00-4) Note P: The classification as a carcinogen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS-No. 200-753-7).

Product does not contain listed SVHC substances > 0,1 % according to Regulation (EC) No. 1907/2006 Article 59 (REACH).

SECTION 4: First aid measures

4.1. Description of first aid measures

according to Regulation (EC) No 1907/2006

C-Quartz UK

Revision date: 28.12.2017 Product code: Page 3 of 12

General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Take off immediately all contaminated clothing.

After inhalation

Remove person to fresh air and keep comfortable for breathing. In case of respiratory tract irritation, consult a physician.

After contact with skin

Take off immediately all contaminated clothing. Wash with plenty of water. In case of skin irritation, seek medical treatment.

After contact with eves

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

After ingestion

Rinse mouth thoroughly with water. Let water be drunken in little sips (dilution effect). Do NOT induce vomiting. Never give anything by mouth to an unconscious person or a person with cramps. In all cases of doubt, or when symptoms persist, seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2). Dry extinguishing powder. alcohol resistant foam.

In case of major fire and large quantities: Atomized water.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Combustible. Vapours may form explosive mixtures with air. In case of fire and/or explosion do not breathe fumes.

Can be released in case of fire: Carbon monoxide Carbon dioxide (CO2). Nitrogen oxides (NOx) Fluorhydric acid. metal oxides.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. In case of fire and/or explosion do not breathe fumes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Use water spray jet to protect personnel and to cool endangered containers.

In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Ventilate affected area.

Do not breathe gas/vapour/aerosol. Avoid contact with skin, eyes and clothes.

Wear personal protection equipment. (See section 8.)

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Cover drains. Prevent spread over a wide area (e.g. by containment or oil barriers). In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

according to Regulation (EC) No 1907/2006

C-Quartz UK

Revision date: 28.12.2017 Product code: Page 4 of 12

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Ventilate affected area.

Treat the recovered material as prescribed in the section on waste disposal.

Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Provide adequate ventilation as well as local exhaustion at critical locations.

Wear suitable protective clothing. (See section 8.)

Advice on protection against fire and explosion

Keep away from sources of ignition. - No smoking. Take precautionary measures against static discharges. Flammable vapours can accumulate in head space of closed systems. In use, may form flammable/explosive vapour-air mixture. Heating causes rise in pressure with risk of bursting.

Further information on handling

General protection and hygiene measures: See section 8.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. Protect against direct sunlight.

Ensure adequate ventilation of the storage area.

Make sure spills can be contained (e.g. sump pallets or kerbed areas).

Advice on storage compatibility

Do not store together with: Gas. Explosives. Flammable solids. Pyrophoric liquids and solids. Self-heating substances and mixtures. Substances and mixtures which, in contact with water, emit flammable gases. Oxidizing liquids. Oxidizing solids. ammonium nitrate. Self-reactive substances and mixtures. Organic peroxides. Non-combustible toxic substances. Radioactive substances. Infectious substances.

Further information on storage conditions

Keep the packing dry and well sealed to prevent contamination and absorbtion of humidity.

Protect against: UV-radiation/sunlight. heat. moisture. frost.

storage temperature: 15-25°C

7.3. Specific end use(s)

refer to chapter 1.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
67-56-1	Methanol	200	266		TWA (8 h)	WEL
		250	333		STEL (15 min)	WEL

8.2. Exposure controls

according to Regulation (EC) No 1907/2006

C-Quartz UK

Revision date: 28.12.2017 Product code: Page 5 of 12









Appropriate engineering controls

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

Protective and hygiene measures

The usual precautions for handling chemicals should be considered.

Keep away from food, drink and animal feedingstuffs.

Always close containers tightly after the removal of product. When using do not eat, drink, smoke, sniff. Wash hands before breaks and after work. Protect skin by using skin protective cream. Take off contaminated clothing.

Eye/face protection

Wear safety glasses; chemical goggles (if splashing is possible). DIN EN 166

Hand protection

In case of prolonged or frequently repeated skin contact: Wear suitable gloves. (DIN EN 374)

Suitable material: Butyl rubber.
Thickness of glove material: 0,5 mm

Breakthrough time >= 480 min. penetration time (maximum wearing period): ~ 120 min. (estimated)

In the case of wanting to use the gloves again, clean them before taking off and air them well. Before using check leak tightness / impermeability.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing.

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500.

Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required.

Respiratory protection necessary at:

Generation/formation of aerosols

exceeding exposure limit values

Insufficient ventilation.

Suitable respiratory protective equipment: gas filtering equipment (EN 141). Type: AX

The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190).

Environmental exposure controls

Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid
Colour: transparent
Odour: characteristic

Test method

pH-Value: not determined

Changes in the physical state

according to Regulation (EC) No 1907/2006

C-Quartz UK

Revision date: 28.12.2017 Product code: Page 6 of 12

Melting point: not applicable
Initial boiling point and boiling range: >100 °C N/A

Flash point: 58 °C

Explosive properties

In use, may form flammable/explosive vapour-air mixture.

Lower explosion limits:

Upper explosion limits:

Ignition temperature:

Decomposition temperature:

not determined

not determined

not determined

Oxidizing properties

none.

Vapour pressure: not determined

(at 20 °C)

Density: not determined Water solubility: not determined

Solubility in other solvents

not determined

Viscosity / dynamic: not determined

(at 20 °C)

Viscosity / kinematic: not determined

(at 20 °C)

Vapour density:not determinedEvaporation rate:not determinedSolvent separation test:not determinedSolvent content:not determined

9.2. Other information

Solid content: not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

No information available.

10.4. Conditions to avoid

Protect against: UV-radiation/sunlight. heat. moisture.

In use may form flammable/explosive vapour-air mixture.

Heating causes rise in pressure with risk of bursting.

10.5. Incompatible materials

Materials to avoid: Oxidizing agents, strong. Reducing agents, strong.

10.6. Hazardous decomposition products

Can be released in case of fire: Carbon monoxide Carbon dioxide (CO2). Nitrogen oxides (NOx) Fluorhydric acid. metal oxides.

SECTION 11: Toxicological information

according to Regulation (EC) No 1907/2006

C-Quartz UK

Revision date: 28.12.2017 Product code: Page 7 of 12

11.1. Information on toxicological effects

Toxicocinetics, metabolism and distribution

No data available.

Acute toxicity

Based on available data, the classification criteria are not met.

The product has not been tested.

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
69430-37-1	Aminoalkoxydimethylpoly	siloxane				
	oral	LD50 mg/kg	>5000	Rat.	read across	
67-56-1	methanol					
	oral	ATE mg/kg	100			
	dermal	ATE mg/kg	300			
	inhalative vapour	ATE	3 mg/l			
	inhalative aerosol	ATE	0,5 mg/l			

Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

Sensitising effects

Based on available data, the classification criteria are not met.

The product is: no danger of sensitization. The statement is derived from the properties of the single components.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

methanol:

Germ cell mutagenicity: Method: OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test). Species: Mouse.; Result: negative. Literature information: ECHA Dossier; Carcinogenicity: Method: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies). Length of test: 18 m. Species: Mouse.; Result: NOAEC = 1,3 mg/l; Literature information: ECHA Dossier; Reproductive toxicity: Method: OECD Guideline 416 (Two-Generation Reproduction Toxicity Study). Species: Rat. Result: NOAEC = 1,3 mg/l; Literature information: ECHA Dossier; Developmental toxicity/teratogenicity: Method: OECD Guideline 414 (Prenatal Developmental Toxicity Study). Species: Rabbit. Result: NOAEL = 1000 mg/kg.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (Stoddard solvent; Low boiling point naphtha - unspecified)

methanol:

Chronic inhalative toxicity: Method: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies). Length of test: 12 m . Exposure time: 20 h/d. Species: Rat.

Result: Result: NOAEC = 1,3 mg/l. Literature information: ECHA Dossier

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

No data available.

according to Regulation (EC) No 1907/2006

C-Quartz UK

Product code: Revision date: 28.12.2017 Page 8 of 12

Further information

Solvent:

Symptoms: Depression of the central nervous system. Liver and kidney damage. drowsiness. vomiting. Nausea. Dizziness. unconsciousness. Impaired consciousness. Intoxication. erythema (redness)

SECTION 12: Ecological information

12.1. Toxicity

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
67-56-1	methanol						
	Acute fish toxicity	LC50 mg/l	15400	96 h	Lepomis macrochirus	ECHA Dossier	
	Acute algae toxicity	ErC50 mg/l	22000		Pseudokirchnerella subca	ECHA Dossier	
	Acute crustacea toxicity	EC50 mg/l	18260	48 h	Daphnia magna	ECHA Dossier	

12.2. Persistence and degradability

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			-
67-56-1	methanol			
	other guideline	76%	20	ECHA Dossier
	Product is biodegradable.			

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-56-1	methanol	-0,7

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

No data available.

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Dispose of waste according to applicable legislation. Consult the local waste disposal expert about waste disposal. Non-contaminated packages may be recycled. According to EAKV, allocation of waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process. Control report for waste code/ waste marking according to EAKV:

Waste disposal number of waste from residues/unused products

200129

MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND INSTITUTIONAL WASTES) INCLUDING SEPARATELY COLLECTED FRACTIONS; separately collected fractions (except 15 01); detergents containing hazardous substances; hazardous waste

according to Regulation (EC) No 1907/2006

C-Quartz UK

Revision date: 28.12.2017 Product code: Page 9 of 12

Waste disposal number of used product

200129 MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND

INSTITUTIONAL WASTES) INCLUDING SEPARATELY COLLECTED FRACTIONS; separately collected fractions (except 15 01); detergents containing hazardous substances; hazardous waste

Waste disposal number of contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND

PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by

hazardous substances; hazardous waste

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN 1993

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (Aminoalkoxydimethylpolysiloxane,

methanol)

14.3. Transport hazard class(es):314.4. Packing group:IIIHazard label:3



Classification code: F1
Special Provisions: 274 601
Limited quantity: 5 L
Excepted quantity: E1
Transport category: 3
Hazard No: 30
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number: UN 1993

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (Aminoalkoxydimethylpolysiloxane,

methanol)

 14.3. Transport hazard class(es):
 3

 14.4. Packing group:
 III

 Hazard label:
 3



Classification code: F1
Special Provisions: 274 601
Limited quantity: 5 L
Excepted quantity: E1

Marine transport (IMDG)

14.1. UN number: UN 1993

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (Aminoalkoxydimethylpolysiloxane,

methanol)

14.3. Transport hazard class(es): 3

according to Regulation (EC) No 1907/2006

C-Quartz UK Revision date: 28.12.2017 Product code: Page 10 of 12

14.4. Packing group: III
Hazard label: 3



Marine pollutant: NO

Special Provisions: 223, 274, 955

Limited quantity: 5 L

Excepted quantity: E1

EmS: F-E, S-E

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1993

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (Aminoalkoxydimethylpolysiloxane,

methanol)

14.3. Transport hazard class(es):314.4. Packing group:IIIHazard label:3



Special Provisions:

Limited quantity Passenger:

Passenger LQ:

Excepted quantity:

A3

10 L

Y344

Excepted quantity:

E1

IATA-packing instructions - Passenger: 355
IATA-max. quantity - Passenger: 60 L
IATA-packing instructions - Cargo: 366
IATA-max. quantity - Cargo: 220 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

See section 8.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not relevant.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 28: Stoddard solvent; Low boiling point naphtha - unspecified 2010/75/EU (VOC):

No information available.

No information available.

No information available.

P5c FLAMMABLE LIQUIDS

(SEVESO III):

Additional information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

REACH 1907/2006 Appendix XVII, No. (mixture): 3

according to Regulation (EC) No 1907/2006

C-Quartz UK

Revision date: 28.12.2017 Product code: Page 11 of 12

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile

work protection guideline' (94/33/EC).

Water contaminating class (D): 3 - highly water contaminating

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

SECTION 16: Other information

Changes

Rev. 1,00, Initial release 25.04.2014

Rev. 1,01, 13.03.2015, Changes in chapter: 2, 3, 7, 8, 16.

Rev. 2,00; 28.12.2017, Changes in chapter: 1-16.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

CAS Chemical Abstracts Service DNEL: Derived No Effect Level

IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals GefStoffV: Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)

LOAEL: Lowest observed adverse effect level

LOAEC: Lowest observed adverse effect concentration

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NOAEL: No observed adverse effect level NOAEC: No observed adverse effect level

NTP: National Toxicology Program

N/A: not applicable

OSHA: Occupational Safety and Health Administration

PNEC: predicted no effect concentration PBT: Persistent bioaccumulative toxic

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de

fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

SARA: Superfund Amendments and Reauthorization Act

SVHC: substance of very high concern TRGS Technische Regeln fuerGefahrstoffe TSCA: Toxic Substances Control Act VOC: Volatile Organic Compounds

VwVwS: Verwaltungsvorschrift wassergefaehrdender Stoffe

WGK: Wassergefaehrdungsklasse

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
STOT RE 2; H373	Calculation method
Aquatic Chronic 3; H412	Calculation method

according to Regulation (EC) No 1907/2006

	C-Quartz UK	
Revision date: 28.12.2017	Product code:	Page 12 of 12

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361f	Suspected of damaging fertility.
H370	Causes damage to organs.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

Further Information

Classification according EC regulation 1272/2008 (CLP): - Classification procedure:

Health hazards: Calculation method.

Environmental hazards: Calculation method.

Physical hazards: On basis of test data and / or calculated and / or estimated.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)